

Universal Interface UI 770





## Universal Interface UI 770

The UI 770 is the ideal universal wideband Interface box which allows the user to connect a PC, standard phone, handset, a headset of the Sennheiser Call center or office series and even a dictaphone for voice recording.

With the UI 770 you can easily switch between the headset, handset and PC, adjust the volume of the headset speaker and mute the headset microphone.

The UI 770 supports the possibility of limiting the Speaker volume by simply setting a switch. This secures compliance with the Noise of work Directive from EU (EU Directive 2003/10/EC) and will result in a reduced maximum output level for the user.

## **Benefits and Features:**

- Dynamic Volume control<sup>™</sup> keeps incoming calls at the same sound level and prevents sudden noises
- Sound clarity system<sup>™</sup> reduces background noise and enhances the caller's voice
- Compatible with both wideband and narrowband headsets and phone systems
- Easy switching option between handset and headset as well as between phone and PC use
- Integrated dictaphone interface for economical and easy call recording
- Compliance with the EU Noise at work
  Directive with a single switch
- Automatic power save function for outstanding battery lifetime of up to 1 year
- Peace of mind 2-year international warranty

## **Product Information**

Product name UI 770
Art. No. 504534

EAN No. 40 44155 080247
UPC No. 6 15104 23184 9
Product description Universal interface box

**Technical Data** 

Speaker signal output to headset
Frequency response 100Hz. to 7kHz
Signal output level max. Limited to 400mV

Microphone signal output to phone

Frequency response 100Hz. to 7kHz

**Signal output level\* at 94dB** OmV. to 300mV. adjustable

Packaging

**Unit Weight** 137 grams/4.9 ounces

**Unit dimensions** 32 x 91 x 101 mm/1.3 x 3.6 x 4 in

Units in distributor master carton 20 pcs

**Master carton weight incl. products** 10.768 kg/23.74 lbs

**Dimensions master carton** 430 x 335 x 330 mm/16.9 x 13.2 x 13 in

Unit pack/end user 1 p

## **Delivery content**

- UI 770 Interface box
- 1.5 volt C-size battery (IEC LR 14 C)
- Phone connecting cable: 4/4 modular plug (RJ9)
- Modular to easy disconnect cable (headset bottom cable)
- Instruction manual